

SKY



Sky is a small and minimal recessed luminaire, square or round, which is ideal for decorative lighting.

Technical Features

- Body from aluminium profile.
- Cover from methacrylate PMMA, 3mm or 8mm in round or square shape.
- Easy mounting with clips.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 70% of the initial luminous flux.
- Connection for operation with Constant Voltage 12V DC.

Upon request:

Available with highest colour rendering index (CRI)

SKY


SKY R8



CE	F	IP 54
0°	0°	min. 12mm
LED	5 YEAR WARRANTY	ta 25°C
		12VDC

- Aluminium body.
- Cover from methacrylate PMMA, 8mm in round shape.

Code	Description	Kg
88077	SKY R8 2,6W	0,080




SKY S8



CE	F	IP 54
0°	0°	min. 12mm
LED	5 YEAR WARRANTY	ta 25°C
		12VDC

- Aluminium body.
- Cover from methacrylate PMMA, 8mm in square shape.

Code	Description	Kg
88075	SKY S8 2,6W	0,080




SKY R3




CE	F	IP 54
0°	0°	min. 12mm
LED	5 YEAR WARRANTY	ta 25°C
		12VDC

- Aluminium body.
- Cover from methacrylate PMMA, 3mm in round shape.

Code	Description	Kg
88076	SKY R3 2,6W	0,070




SKY S3



CE	F	IP 54
0°	0°	min. 12mm
LED	5 YEAR WARRANTY	ta 25°C
		12VDC

- Aluminium body.
- Cover from methacrylate PMMA, 3mm in square shape.

Code	Description	Kg
88010	SKY S3 2,6W	0,070



LED Colour Codes:

- 1 Cold 2 Warm 3 Neutral 4 Blue 5 Yellow 6 Red 7 Green

DIMMER		LED LUMINAIRES DESCRIPTION		N° Luminaires		DIMENSIONS mm		CODE		
				min.	max.					
		SKY (CONSTANT VOLTAGE)	2,6W	1	4	12V DC	13W IP20	160 x 22 x 19	800060	