

**KADRO, CORONA, SOL with CLUB Mini LED**

The trimless CLUB SOL Mini and the elegant deep CORONA & KADRO luminaires highlight impressively premises, such as shopping malls, stores, hotels, exhibition halls, museums etc.

They are compact, in round or square version and efficient and they have excellent colour quality and high-precision light distribution.

Their last generation LED chip in combination with an efficient thermal management ensure the excellent performance of the luminaire and a maximum energy efficiency.

### Technical Features

**- CLUB SOL:**

Trimless recessing frame, in round or square shape, painted electrostatically in selected colour from die-cast aluminium.

**- CORONA CLUB:**

Deep recessing frame, in round or square shape, painted electrostatically in selected colour from die-cast aluminium.

**- KADRO CLUB:**

Deep recessing frame, in square shape, painted electrostatically in selected colour from steel.

- Internal rotatable spot from aluminium profile.

- Easy mounting.

- High efficient lens in Spot, Medium, Wide versions.

- Last generation extra efficient led light sources.

- Pure light without IR/UV radiation.

- Operation life: 50,000 hours with efficiency > 70% of the initial luminous flux.

- Connection for operation with Constant Current.

**Upon request:**

Available with highest colour rendering index (CRI).

KADRO, CORONA, SOL with CLUB Mini LED


KADRO CLUB Mini



CE	F	850°C	IP 40
40°	350°	5-40mm	
LED	500mA	ta 25°C	

- Lens: Spot, Medium, Wide.
- Reflector in Medium version.
- 5W power consumption driven at 500mA.
- Efficiency:  
4000 K: 450 Lumen, CRI: min. 75  
3000 K: 420 Lumen, CRI: min. 80  
Maximum: 90 Lm/W

Code	Description	Kg
86733	KADRO CLUB MINI LED 5W (driver not included)	0,400
86736	KADRO CLUB MINI LED 5W Reflector (driver not included)	0,400




CORONA CLUB Mini



CE	F	850°C	IP 40
40°	350°	12,5mm	
LED	500mA	ta 25°C	

- Lens: Spot, Medium, Wide.
- Reflector in Medium version.
- 5W power consumption driven at 500mA.
- Efficiency:  
4000 K: 450 Lumen, CRI: min. 75  
3000 K: 420 Lumen, CRI: min. 80  
Maximum: 90 Lm/W

Code	Description	Kg
86731	CORONA CLUB MINI LED 5W (driver not included)	0,500
86734	CORONA CLUB MINI LED 5W Reflector (driver not included)	0,500




CORONA Q CLUB Mini



CE	F	850°C	IP 40
40°	350°	12,5mm	
LED	500mA	ta 25°C	

- Lens: Spot, Medium, Wide.
- Reflector in Medium version.
- 5W power consumption driven at 500mA.
- Efficiency:  
4000 K: 450 Lumen, CRI: min. 75  
3000 K: 420 Lumen, CRI: min. 80  
Maximum: 90 Lm/W

Code	Description	Kg
86732	CORONA Q CLUB MINI LED 5W (driver not included)	0,650
86735	CORONA Q CLUB MINI LED 5W Reflector (driver not included)	0,650



KADRO, CORONA, SOL with CLUB Mini LED


CLUB SOL Mini



CE	F	850°C	IP 40
50°	350°	12.5mm	
LED	500mA	ta 25°C	

- Lens: Spot, Medium, Wide.
- Reflector in Medium version.
- 5W power consumption driven at 500mA.
- Efficiency:  
4000 K: 450 Lumen, CRI: min. 75  
3000 K: 420 Lumen, CRI: min. 80  
Maximum: 90 Lm/W

Code	Description	Kg
86891	CLUB-SOL MINI LED 5W (driver not included)	0,500
86890	CLUB-SOL MINI LED 5W Reflector (driver not included)	0,500




CLUB SOL Q Mini



CE	F	850°C	IP 40
50°	350°	9.5mm, 12.5mm, 15.0mm	
LED	500mA	ta 25°C	

- Lens: Spot, Medium, Wide.
- Reflector in Medium version.
- 5W power consumption driven at 500mA.
- Efficiency:  
4000 K: 450 Lumen, CRI: min. 75  
3000 K: 420 Lumen, CRI: min. 80  
Maximum: 90 Lm/W

Code	Description	Kg
86892	CLUB-SOL Q MINI LED 5W (driver not included)	0,650
86893	CLUB-SOL Q MINI LED 5W Reflector (driver not included)	0,650



LED COLOUR CODES:

2 Warm 3 Neutral

BEAM CODES:

01 spot 02 medium 03 wide

Colour Codes:

0 Colours 1 White 2 Titan 3 Black

DRIVERS						
LED LUMINAIRES DESCRIPTION	N° Modules min. max.		DIMENSIONS mm			
					CODE	
KADRO, CORONA, SOL with CLUB Mini LED 5W	1	1	500mA 6W IP20	70 x 35 x 21		800024
KADRO, CORONA, SOL with CLUB Mini LED 5W	2	3	500mA 16W IP20	115 x 45 x 27,5		800031

DIMMER DRIVERS						
LED LUMINAIRES DESCRIPTION	N° Modules min. max.		DIMMER TYPE	DIMENSIONS mm		
						CODE
KADRO, CORONA, SOL with CLUB Mini LED 5W	1	3	500mA 22W IP20	1-10Vdc/Push Button	145 x 40 x 28	
						800040



