

SOFT LIGHT L 670

A recessed 600x600mm luminaire with special geometrical structure. The combination of the parabolic louvre and the micro-perforated reflector gives a direct-indirect light distribution, suitable for environments where diffuse and soft light is required for optimal visual comfort.

Technical Features

- Recessed luminaire for panels in mineral fibre with expose structure or plasterboard ceiling 600x600mm.
- Steel body painted electrostatically.
- Steel parabolic recuperator with high reflectivity in white colour.
- Micro-perforated reflector, from steel, painted in white colour, covered with reflection film.
- Parabolic louvre from specular aluminium.
- Connection for operation on 230V-50/60Hz with electronic ballast.

Upon Request

- Connection for operation on 230V-50/60Hz with dimmer dali or 1-10VDC ballast.
- Connection for emergency lighting system.

SOFT LIGHT L 670


SOFT LIGHT L 670




CE	F	⊕	IP 20
TC-L			
2G11			
		Included	

- Version for TC-L/2G11.
- Steel parabolic recuperator with high reflectivity in white colour.
- Micro-perforated reflector.
- Parabolic louvre.
- Suspension brackets not included.

Code	Description
354493	Soft Light L 672x40W
354523	Soft Light L 672x55W



ACCESSORIES - SUSPENSION BRACKETS



CE			

- Suspension brackets from galvanized steel thickness 1,5mm, necessary for the installation in plasterboard.
- **15 BS** min.18mm, max. 45mm
- **15 ZH** min.45mm, max. 72mm

Code	Description
303001	15 BS (4 pieces)
303005	15 ZH (4 pieces)

