

**SLICE**

The SLICE surface-mounted luminaire with its opal cover provides perfect lighting comfort and uniform, glare-free lighting. The luminaire unit impresses with its low profile, while slim-line design is emphasised by its linear contours.

**Technical Features**

- Steel body painted electrostatically.
- High efficient satin PMMA cover.
- Last generation high efficient LED CHIP.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 70% of the initial luminous flux.
- Connection for operation on 230V-50/60Hz with electronic ballast.

**Upon Request**

- Connection for operation on 230V-50/60Hz with dimmer dali or 1-10VDC ballast.


SLICE

SLICE



- Version for LED CHIP.
- High efficient satin PMMA cover.

Code	Description
29301	Slice Q Led 36W 5000 lm Neutral
29302	Slice Q Led 36W 5000 lm Warm
29303	Slice Q Led 65W 8750 lm Neutral
29304	Slice Q Led 65W 8750 lm Warm
29305	Slice Led 56W 6200 lm Neutral
29306	Slice Led 56W 6200 lm Warm
29307	Slice Led 65W 8800 lm Neutral
29308	Slice Led 65W 8800 lm Warm



Colour Codes:

- 0 Colours
  1 White
  2 Titan

