

OSRAM: T8  
PHILIPS: TL-D

**Diffuser** in methacrylate, injection moulded, multilenticular, anti-glare.

**ZERO 3F IP54**  
(SURFACE MOUNTED LUMINAIRES)

850°C

IP 54

6,5J

				PRICE LIST			
DESCRIPTION	DIMENSIONS	COLOUR	Conventional ballast and capacitor		Electronic ballast		
			CODE	PRICE	CODE	PRICE	
03F 1x18W T26 IP54	110 x 640 x 85	White	551012		551013		
03F 1x36W T26 IP54	110 x 1250 x 85	White	551112		551113		
03F 1x58W T26 IP54	110 x 1550 x 85	White	551152		551153		
03F 2x18W T26 IP54	210 x 640 x 68	White	551022		551023		
03F 2x36W T26 IP54	210 x 1250 x 68	White	551122		551123		
03F 2x58W T26 IP54	210 x 1550 x 68	White	551162		551163		
03F 4x18W T26 IP54	640 x 640 x 68	White	551042		551043		

OSRAM: T8  
PHILIPS: TL-D

OSRAM: T9  
PHILIPS: TL-E

**Diffuser** in opal methacrylate.

**UNO**  
(SURFACE MOUNTED LUMINAIRES)

IP 40

650°C

CE

				PRICE LIST			
DESCRIPTION	DIMENSIONS	COLOUR	Conventional ballast and capacitor		Electronic ballast		
			CODE	PRICE	CODE	PRICE	
UNO 162x18W T26	210 x 640 x 68	White	211022		211023		
UNO 162x36W T26	210 x 1250 x 68	White	211122		211123		
UNO 164x18W T26	640 x 640 x 68	White	211042		211043		
UNO 161x22W T-R	350 x 350 x 68	White	211572		211573		
UNO 161x32W T-R	350 x 350 x 68	White	211582		211583		
UNO 161x40W T-R	450 x 450 x 68	White	211592		211593		
UNO 162x32W+40W T-R	450 x 450 x 68	White	211602		211603		

**Wire-guard** for applications in dry environments, against shocks coming from any directions, in galvanized steel rod Ø5mm.

**SURFACE MOUNTED LUMINAIRES ACCESSORY**

			PRICE LIST	
CODE	DESCRIPTION	DIMENSIONS		
201302	<b>12 AZ</b> (for lum. 36W T26, 28/54W T16)	180 x 1320 x 130		
201301	<b>12 BX</b> (for lum. 36W T26, 28/54W T16)	280 x 1330 x 130		
201303	<b>12 IA</b> (for lum. 58W T26, 35/49/80W T16)	180 x 1630 x 130		
201304	<b>12 LB</b> (for lum. 58W T26, 35/49/80W T16)	280 x 1630 x 130		